



*Luxury with Reliability*



**MASTER MOTOR CORP. (PVT.) LTD.**

**UAN: 111-MASTER (021-111-627-837)**

## SPECIFICATIONS

Dimension		Displacement		10.338L	Accessories	
Overall Length	12000 mm	Max. Horse Power	340 PS/1900rpm (Max Hp=Rated powerx1.35)		Luggage Compartment Space	9.5 m'
Overall Width	2500 mm	Rated Power	Speed: 250Kw/1900rpm		Interior Trimming	Soft Interior trimming integral A/C Channel
Overall Height	3600 mm	Max. Torque	1550N.m±6%/1100-1500 rpm		Luggage Carrier	Integral interior luggage carrier
Interior Height	1990 mm	Emission	Euro-III		First Passenger Door	First Single Leaf Swing out Door
Wheel Base	6050 mm	<b>Transmission</b>				
Overhang (Frame) Front (FOH)	2620 mm	Model	QIJIANG S6-160		Safety Door	Safety door on the right side
Overhang (Frame) Rear (ROH)	3330 mm	1st Gear	7.030		Seats	49+1+1 All seats with seat belts
Tread Front (TF)	2070 mm	2nd Gear	4.090		A/C	Kelin A/C, 32000 kcal/h, Bock compressor
Tread Rear (TR)	1860 mm	3rd Gear	2.450		Heating Equipment	Heater
<b>Weight</b>		4rd Gear	1.500		Defrosting	Defrosting System
Permissible (G.V.W)	18000 kg	5th Gear	1.000		Rear View Mirror	Electrical rear View mirror (Automatically heating)
Kurb Weight	13300 kg	6th Gear	0.810		Sunshield Curtain	Blue soft fabric curtain
On Front Axle	6250 kg	rev. Gear	6.480		Fire Extinguisher	1 Pcs 2kg fire extinguisher
On Rear Axle	11750 kg	<b>Steering</b>				
<b>Performance</b>		Operation	Power			
Max. Speed	125 Km/h	Make	ZF		<b>Additional Accessories</b>	
Min. Turning Radius	11 m	<b>Axle</b>			4 CCTV Camera	
Gradeability	38%	Front Axle	Dongfeng Axle		Call Bell	
<b>Clutch</b>		Capacity	6250 kg		Fridge	
Type	Dry, Single Plate Hydraulic Distance control Central Air Assisted	Rear Axle	Jing Yida		USB Mobile Charger	
<b>Frame</b>		Capacity	11750 kg		Electrical Clock	
Type	Semi-monocoque	Final Gear Ratio	3.15		Blue Tooth Airphone	
<b>Fuel Tank</b>		Service	Seperate dual circuit air brake system		Yutong proprietary Engine Thermal Management System	
Capacity	410 L	ABS	WABCOABS + Haldex Auto slack adjuster		Eddy current retarder, with temperature warning device	
<b>Suspension</b>		<b>Tire &amp; Wheel</b>			CAN system	
Air Suspension, 6 Bellows		Tire	6+1 (295 R 22.5)		Automatic fire extinguishing bomb in the engine compartment	
<b>Engine (Rear)</b>		<b>Electric System</b>			Reverse color monitor	
Model	YC6MK340-30	Battery	2 x 12 Volts		Remote control locker of passenger door	
Type	Diesel, 6 Cylinders, Water Intercooler Turbo Charged	Alternator	24V DC/150 AMP		Auto Greasing System	
Bore & Stroke	123 x 145 mm	Starter	24V DV/7.5 KW			