

D-330/380

AUMAN ETX dump trucks feature a classic powertrain and advanced technologies, which includes the World's leading transmissions and engines. AUMAN ETX dump trucks have proven to be extremely reliable.



D-330 6x4 Dump Truck | 330PS | 41 Ton GVW

D-380 8x4 Dump Truck | 380PS | 50 Ton GVW



**TECHNOLOGY
LEADING INTO THE FUTURE.**



PRODUCT TECHNICAL DATA

Function		Dumper - ETX	Dumper - ETX	Dumper - ETX	
Vehicle Model		D-330 (SWB)	D-330 (LWB)	D-380	
Driveline		6x4	6x4	8x4	
Dimension Parameters	Overall Dimensions (L x Wx H) (mm)	8557 x 2495 x 3400	8870 x 2495 x 3400	11592 x 2495 x 3400	
	Cargo Body Dimensions (L x Wx H) (mm)	5600 x 2300 x 1500	6000 x 2300 x 1500	8600 x 2300 x 1500	
	Wheel Base	3825+1350	4100+1350	1800+4700+1350	
Mass Parameters	Kerb Weight of Chassis (kg)	12,495	14,000	15,760	
	Rated Payload (kg)	19,310	19,305	25,045	
	GVW (kg)	32,000	33,500	41,000	
	MAX. GVW (kg)	41,000	43,000	50,000	
Main Configurations	Engine	Brand	Wei Chai	Wei Chai	Wei Chai
		Model	WD615.44	WD615.44	WP12.380E32
		Max Power (kW/P.S. @ rpm)	243/330 @ 2200	243/330 @ 2200	280/380 @ 2200
		Max Torque (kgf.m @ rpm)	127.5 @ 1400-1600	127.5 @ 1400-1600	153 @ 1300-1600
		Displacement (cc)	9726	9726	11596
		Emission	EURO II	EURO II	EURO III (EGR)
	Gear Box	Brand	FAST (9+1)	FAST(12+2)	FAST(12+2)
		Model	9JSD150T-B (PTO)	12JSD160T (PTO)	12JSD180TA (PTO)
		Gear ratios	1 : 12.65, 2 : 8.38, 3 : 6.22 4 : 4.57, 5 : 3.4, 6 : 2.46 7 : 1.83, 8 : 1.34, 9 : 1.00, R : 13.22	1 : 15.53, 2 : 12.08, 3 : 9.39 4 : 7.33, 5 : 5.73, 6 : 4.46 7 : 3.48, 8 : 2.71, 9 : 2.1, 10 : 1.64, 11 : 1.28, 12 : 1.00, R1 : 14.86, R2 : 3.33	1 : 12.10, 2 : 9.41, 3 : 7.31 4 : 5.71, 5 : 4.46, 6 : 3.48 7 : 2.71, 8 : 2.11, 9 : 1.64, 10 : 1.28, 11 : 1.00, 12 : 0.78, R1 : 11.56, R2 : 2.59
			Clutch Plate Diameter (mm)	430	430
	Front Axle (kg)	9000	9000	2x9,000	
	Rear Axle (kg)	2X16,000	2X16,000	2X16,000	
	Final Gear Ratio	5.73 (double reduction)	5.73 (double reduction)	5.26 (double reduction)	
	Brake Type	Service Brake	Dual Circuit Pneumatic Brake		
		Parking Brake	Energy Accumulating Spring Air cut-off Brake		
		Auxiliary Brake	The Engine Exhaust Brake		
	Suspention	Front	Longitudinal leaf spring with dual acting telescopic shock absorbers and anti-roll bar/13+14		
		Rear	Longitudinal leaf spring, balanceSuspension and anti-roll bar/12		
	Steering Gear Model		ZF8098		
	Tyre		12.00-R20 (10+1)		12.00-R20 (12+1)
	Fuel Tank Capacity (L)		350		

*Specifications are with normal manufacturing allowances & are subject to change without prior notice due to our on-going research & development program or to meet local & Government requirements. Original product may vary from the one presented in this flyer.